

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29CFR 1910.1200

Rev. 09/02/09

TIN /SILVER SOLDER

96.5 Sn/3.5 Ag

96 Sn/4 Ag

BELLMAN-MELCOR, LLC
7575 183RD ST.
TINLEY PARK, IL 60477

Phone: 800-367-6024
Infotrac Emergency No. 1-800-535-5053

1. PRODUCT INGREDIENTS

ChemicalName	CASNumber	Weight %	Permissible Air Concen.(mg/cu.m.)		SARA Title III Sect.313Chem.
			OHSA	ACGIH	
TIN	7440-31-5	94-99	2.0	2.0	NO
SILVER	7440-22-4	1-6	0.01	0.01	YES

This product contains less than 0.10% Lead

2. PHYSICAL DATA

Material is SOLID	Appearance and Odor SILVER-WHITE METAL WIRE, ODORLESS		
Melting Point METAL-APPROX. 221 C	Boiling Point 2250 C	Specific Gravity 7.1	Vapor Density N/A
Solubility in Water INSOLUBLE	Vapor Pressure N/A	Evaporation Rate N/A	pH N/A

3. FIRE AND EXPLOSION DATA

Flash Point METAL N/A	Flammable Limits N/A	Auto Ignition Temp. N/A
--------------------------	-------------------------	----------------------------

Unusual Fire and Explosion Hazards
WHEN HEATED OR IN CONTACT WITH ACIDS, CAN EMIT TOXIC FUMES

Fire Extinguishing Agents Recommended
USE CO2 OR DRY CHEMICAL ON SURROUNDING FIRE

Fire Extinguishing Agents To Avoid
DO NOT USE WATER ON FIRE WHERE MOLTEN METAL IS PRESENT

Special Fire Fighting Precautions
N/A

4. HEALTH HAZARD INFORMATION

Primary Routes of Entry INGESTION	X INHALATION	ABSORPTION
--------------------------------------	--------------	------------

Carcinogenicity

THIS PRODUCT HAS NOT BEEN LISTED AS A SUSPECT CARCINOGEN BY NPT, IARC OR OSHA.

Acute Overexposure (symptoms and effects)

INHALATION MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT. EYE CONTACT BY FUMES MAY CAUSE IRRITATION. SKIN CONTACT MAY CAUSE IRRITATION.

5. PRECAUTIONS/PROCEDURES

OVERHEATING OF ALLOY CAN PRODUCE METAL FUMES AND OXIDES. MACHINING OPERATIONS SUCH AS GRINDING, SAWING OR BUFFING CAN GENERATE AIRBORN PARTICULATES IN THE WORK AREA. EXPOSURE LEVELS INDICATED IN SECTION 1 ARE RELEVANT TO THESE AND OTHER OPERATIONS.

Normal Handling:

USE OF APPROVED RESPIRATORS IS REQUIRED FOR APPLICATIONS WHERE ADEQUATE VENTILATION CANNOT BE PROVIDED. ACTIVITIES WHICH GENERATE DUST OR FUME SHOULD BE AVOIDED. WHEN MELTED, THE TEMPERATURE SHOULD BE KEPT AS LOW AS POSSIBLE.

Spill or Leak:

ANY METHOD THAT KEEPS DUST TO A MINIMUM IS ACCEPTABLE. VACUUMING IS PREFERRED. USE OF APPROVED RESPIRATORY PROTECTION WHERE POSSIBILITY OF DUST/FUME EXPOSURE EXISTS. DO NOT USE COMPRESSED AIR FOR CLEANING.

Personal Hygiene:

AVOID INHALATION OR INGESTION. PRACTICE GOOD HOUSEKEEPING AND PERSONAL HYGIENE PROCEDURES.

Engineering Controls:

LOCAL EXHAUST VENTILATION IS RECOMMENDED FOR DUST AND/OR FUME GENERATION OPERATIONS WHERE AIRBORNE EXPOSURES MAY EXCEED PERMISSIBLE AIR CONCENTRATIONS.

Storage:

GENERAL STORAGE PROCEDURES ACCEPTABLE.

Special Precautions, Procedures and Label Instruction:

SPECIAL ATTENTION IS DRAWN TO THE REQUIREMENTS OF THE OSHA RESPIRATOR STANDARD (1910.134) SHOULD AIRBORNE EXPOSURES EXCEED THE OSHA ACTION LEVEL OR PEL.

6. PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection:

WHERE AIRBORNE EXPOSURES MAY EXCEED OSHA/ACGIH PERMISSIBLE AIR CONCENTRATIONS, THE MINIMUM RESPIRATORY PROTECTION RECOMMENDED IS A NEGATIVE PRESSURE AIR PURIFYING RESPIRATOR WITH CARTRIDGES THAT ARE NIOSH/MSHA APPROVED AGAINST DUST, FUMES AND MISTS HAVING A TWA NOT LESS THAN 0/05 MG/CU M.

